

# PecoSlick 607™

Liquid PHPA

Oil & Gas Drilling Fluids / WBM



**PecoSlick 607™** is a proprietary aqueous emulsion of anionic polyacrylamide / polyacrylate copolymer used to stabilize clay and shale formations and as a viscosifier. **PecoSlick 607™** can be used in fresh or brackish waters. **PecoSlick 607™** mixes easily and requires minimum shear to achieve full effectiveness.

## PROPERTIES, TYPICAL

Appearance..... Thick Opaque White Liquid  
Specific Gravity, g/cc ..... 1.04  
pH, 2% in Water ..... 6-8  
Freeze Point, °F ..... 5.0

## ADVANTAGES

- Reduces bit-balling
- Aids in lubrication
- Increases the yield of Bentonite
- Increases viscosity without adding solids
- Non-fermenting

## PACKAGING

- 5 Gal Pails (36 Pails / Pallet)
- 55 Gal Drum
- 275 Gal Tote



The information contained on this page is correct to the best of our knowledge, but is intended only as a source of information. The recommendations or suggestions herein are made without guarantee or representation as to results, and we suggest that you evaluate the recommendation contained on this page in your own laboratory prior to use. Our responsibility for claims arising from breach of warranty, negligence or otherwise is limited to the purchase price of the material.